

SUPPLEMENTAL LABEL
FOR DISTRIBUTION AND USE ONLY WITHIN THE STATE OF ARKANSAS

TOMAHAWK 4

EPA REG. NO. 33270-18

**TOMAHAWK 4 TANK MIX WITH COMMAND 3ME AND WITH OR WITHOUT
SHARPEN HERBICIDES FOR AERIAL APPLICATION ON RICE.**

- This labeling must be in the possession of the user at the time of pesticide application.
- It is a violation of Federal law to use this product in a manner inconsistent with its labeling.
- All applicable directions, restrictions, and precautions on all EPA registered labels, Command 3ME SLN AR08-0001 label and Sharpen EPA Reg. No. 7969-278 are to be followed. Refer to all labels for use instructions, weeds controlled, and application instructions.

THIS LABEL FOR TOMAHAWK 4 IS VALID UNTIL WITHDRAWN, CANCELLED OR SUSPENDED.

KEEP OUT OF REACH OF CHILDREN
CAUTION

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in any manner inconsistent with its labeling. This labeling must be in the possession of the user at the time of herbicide application.

AVOID CONTACT OF HERBICIDE WITH FOLIAGE, GREEN STEMS, EXPOSED NON-WOODY ROOTS OR FRUIT OF CROPS (EXCEPT AS SPECIFIED FOR INDIVIDUAL ROUNDUP READY® CROPS), DESIRABLE PLANTS AND TREES, BECAUSE SEVERE INJURY OR DESTRUCTION MAY RESULT.

See "GENERAL INFORMATION" and "MIXING" sections of the label booklet for TOMAHAWK 4 for essential product performance information.

DO NOT ALLOW SPRAY TO DRIFT FROM THE APPLICATION SITE. DO NOT APPLY INTO STILL AIR WHERE THERE IS A TEMPERATURE INVERSION LAYER LOW ENOUGH FOR FINE SPRAY PARTICLES TO BECOME SUSPENDED AND MOVE OUTSIDE THE TARGET AREA WHEN THE INVERSION LAYER MOVES. DO NOT APPLY WHEN WINDS ARE GUSTY OR UNDER ANY OTHER CONDITION THAT FAVORS DRIFT. DRIFT IS LIKELY TO CAUSE DAMAGE TO ANY VEGETATION

CONTACTED. TO PREVENT INJURY TO ADJACENT DESIRABLE VEGETATION, APPROPRIATE BUFFER ZONES MUST BE MAINTAINED.

Use the recommended rate of this product in 3 to 10 gallons of water per acre.

Use sufficient carrier volume and appropriate equipment setup to form droplets large enough to avoid drift potential. Coarse droplets in the 300 to 500 (VMD) micron range are recommended.

Applications should typically be made with the nozzle release point at 10 to 15 feet above the top of the target plants unless a greater height is required for aircraft safety.

The distance of the outermost nozzles on the boom must not exceed 75 percent of the length of the wingspan or rotor.

Do not apply this product when winds are in excess of 10 mph.

Do not apply when there is a low-level inversion where fine spray particles could be suspended in still air and move outside the target area when the inversion layer moves. These conditions may occur when wind speeds are less than 2 mph.

Do not apply if wind conditions favor drift toward crops or desirable vegetations.

Read the "Limit of Warranty and Liability" in the label booklet for TOMAHAWK 5 before using. These terms apply to this supplemental labeling and if these terms are not acceptable, return the product unopened at once.